



- 产品类型：照明端子,
- 接线方式：线对线端子,
- 工作温度：Max.40℃,
- 线径：28-12AWG/0.08-2.5mm²,
- 剥线长度: 9-10mm
- 位数：2P , 3P , 5P

基本参数

电压(Rated voltage)-UL:	-
电流(Rated current)-UL:	-
电压(Rated voltage)-IEC:	400V
电流(Rated current)-IEC:	32A
线径(Wire range)-UL:	28-12AWG
线径(Wire range)-IEC:	0.08-2.5mm ²
剥线长度(Wire stripping length):	9-10mm / 0.35-0.39inches
材质(Material quality):	PA66
阻燃等级(Flame Rating):	UL94-V0
导体材料(Conductor material):	铝 , 铜
位数(Pole number):	2P , 3P , 5P
使用温度(Operating temperature):	Max.40℃
认证(Approval):	

尺寸图
订购产品

产品名称	线径	位数	产品型号	3D下载	2D下载
线对线端子222-2	28-12AWG/0.08-2.5mm ²	2P	222-2-2P		
线对线端子222-2	28-12AWG/0.08-2.5mm ²	3P	222-2-3P		
线对线端子222-2	28-12AWG/0.08-2.5mm ²	5P	222-2-5P		

资料下载

产品目录	接线端子选型手册
------	--------------------------