








- SL数据连接器系列，
- SL12, SL16, SL20, SL24 四个规格，
- 结构类型：组装直式插头，
- 插针类型：针型，
- 连接方式：螺纹，
- 芯数：2-35，
- 接线方式：焊接，
- 屏蔽：否，
- 认证：TUV&UL，

机械参数

□□□□□		PBT
□□□□□		□□□□
□□□□□		□□/□□
□□□□□		□□□
□□□□□		□□
□□□□□		≥500□(Cycles)
□□□□□		-25°C ~ +85°C
□□□□ □		标配 IP65 / 可选 IP67 & IP68
认证标准□		符合TUV和UL认证标准

电气参数

芯数 Number of contact	2	3	4	10	12	19	24
公端绝缘体正面图 Male contact face view							
额定电流(A) Rated current	25	25	25	10	10	5	5
工作电压(AC.V) Rated voltage	500	500	500	400	400	250	250
耐压(AC.V) 1 min Test voltage	2000	2000	2000	1500	1500	1000	1000
接触电阻(mΩ) Contact resistance	1	1	1	3	3	5	5
接触件直径(mm) Contact diameter	φ 3.0x2	φ 3.0x3	φ 3.0x4	φ 1.5x10	φ 1.5x12	φ 1.0x19	φ 1.0x24
导体规格(mm²/AWG) Wire size	4.0/12	4.0/12	4.0/12	1.5/16	1.5/16	0.5/20	0.5/20
适用线径 Cable O.D range	≤ φ 13.5mm						
机械寿命 Mechanical life	≥500 次(times)						
接线方式 Assembly style	焊接(Soldering)						
防护等级 Protection level	标配 IP65 / 可选 IP67 & IP68 (Standard is IP65, IP67 & IP68 Option Avaliable)						
工作温度 Temperature rating	-25℃ ~ +85℃						
外壳/绝缘部分 Shell & insulated parts	PBT						
金属部分 Hardware metal	锌合金(Zinc Alloy)						
接触铜针 Contact size	铜合金(Brass with gold-plated)						
防水材料 Sealing	硅胶/橡胶(Silicone/rubber)						
认证标准 Approval standards	符合TUV和UL认证标准						

订购产品

产品名称	额定电压	额定电流	耐压	芯数	产品型号	3D下载	2D下载
SL24直式针型插头	500V	25A	2000	2	SL24-A-P		↓
SL24直式针型插头	500V	25A	2000	3	SL24-A-P		↓
SL24直式针型插头	500V	25A	2000	4	SL24-A-P		↓
SL24直式针型插头	400V	10A	1500	10	SL24-A-P		↓
SL24直式针型插头	400V	10A	1500	12	SL24-A-P		↓
SL24直式针型插头	250V	5A	1000	19	SL24-A-P		↓
SL24直式针型插头	250V	5A	1000	24	SL24-A-P		↓