


M8 Male Front Mount Socket (Solder, Screw M8*0.5, Metal interface)

尺寸图



接线定义

芯位 Pins	线芯颜色 Wire core color			
	3芯(Pins)			
1	BN			
2	-			
3	BU			
4	BK			

芯位 Pins	线芯颜色 Wire core color			
	4芯A编码(4 Pins A-Code)		4芯D编码(4 Pins D-Code)	
1	BN		YE	
2	WH		WH	
3	BU		OG	
4	BK		BU	

芯位 Pins	线芯颜色 Wire core color			
	5芯A编码(5 Pins A-Code)		5芯B编码(5 Pins B-Code)	
1	BN		BN	
2	WH		WH	
3	BU		BU	
4	BK		BK	
5	GY		GY	



芯位 Pins	线芯颜色 Wire core color	
	6芯(Pins)	
1	BN	
2	WH	
3	BU	
4	BK	
5	GY	
6	PK	

芯位 Pins	线芯颜色 Wire core color	
	8芯(Pins)	
1	WH	
2	BN	
3	GN	
4	YE	
5	GY	
6	PK	
7	BU	
8	RD	

*接线定义按常规标准，如按协议或者其他请联系我司业务。
Wiring definition according to conventional standards, if according to the agreement or other please contact our sales.

电气参数

M8 Male Front Mount Socket (Solder, Screw M8*0.5, Metal interface)

芯数 Pins	针型 Male			额定电流 Ratedcurrent	额定电压 Rated voltage		导体规格 Conductor size		孔型 Female			
	A	B	D		A/C	D/C	AWG	mm ²	A	B	D	
3				3A	60V	60V	24	0.25				
4				A型(A-Code): 3A D型(D-Code): 4A	A型(A-Code): 60V D型(D-Code): 48V	60V	24	0.25				
5				3A	30V	30V	24	0.25				
6				A型(A-Code): 1.5A D型(D-Code): 1.5A/ 3A		30V	30V	26	0.14			
8				1.5A		30V	30V	26	0.14			