




- 产品类型：PCB端子,
- 接线方式：弹簧连接,
- 间距：15mm,
- 电压：600V,
- 电流：120A,
- 位数：2-10P

基本参数

间距(Pitch):	15mm
电压(Rated voltage)-UL:	600V
电流(Rated current)-UL:	120A
电压(Rated voltage)-IEC:	1000V
电流(Rated current)-IEC:	125A
线径(Wire range)-UL:	20-2AWG
线径(Wire range)-IEC:	0.5-35mm ²
位数(Pole number):	02~10P
绝缘材料(Insulation Material):	PA66 UL94 V-0
电流承载部件材料和镀层(Material & Plating of Current carrier):	Copper alloy, Tin plated
绝缘电阻(Insulation Resistance):	500MΩ or more at DC500V
耐电压(1分钟)(Withstanding Voltage/1Min):	4200V
额定冲击电压(Rated surge voltage):	-
接线螺丝(Wire clamp unit Screw), 最大扭矩(torque Max.):	M5, 2.0Nm Max
接线弹片材料(Material of Clamp spring):	-
剥线长度(Wire stripping length):	18-19mm
使用温度(Operating temperature):	-40℃ ~ +105℃
焊接方式(Soldering recommend):	Wave soldering, 260℃ 5S Max(Single Wave), 260℃ 10S Max(Double Wave)
认证(Approval):	

尺寸图



订购产品

产品名称	间距	位数	产品型号	3D下载	2D下载
固定式端子	15mm	02~10P	SA1500-03M		

资料下载

产品目录	接线端子选型手册
------	--------------------------