




- 产品类型：插拔式端子,
- 接线方式：弹簧连接,
- 间距：3.50mm,
- 电压：300V,
- 电流：8A,
- 位数：4-48P

## 基本参数

间距(Pitch):	3.50mm
电压(Rated voltage)-UL:	300V
电流(Rated current)-UL:	8A
电压(Rated voltage)-IEC:	160V
电流(Rated current)-IEC:	10A
线径(Wire range)-UL:	-
线径(Wire range)-IEC:	-
位数(Pole number):	04~48P
绝缘材料(Insulation Material):	PA9T/LCP UL94 V-0
电流承载部件材料和镀层(Material & Plating of Current carrier):	Copper alloy, Tin plated
绝缘电阻(Insulation Resistance):	500MΩ or more at DC500V
耐电压(1分钟)(Withstanding Voltage/1Min):	1600V
额定冲击电压(Rated surge voltage):	-
接线螺丝(Wire clamp unit Screw), 最大扭矩(torque Max.):	-
固定螺丝(Mounting Screw), 扭矩(torque):	-
接线弹片材料(Material of Clamp spring):	-
剥线长度(Wire stripping length):	-
使用温度(Operating temperature):	-40°C ~ +130°C
焊接方式(Soldering recommend):	Wave soldering & Reflow soldering (THR) capable
认证(Approval):	

## 尺寸图



## 订购产品

产品名称	间距	位数	产品型号	3D下载	2D下载
插拔式端子	3.50mm	04~48P	SPA350-D07L		

## 资料下载

产品目录	<a href="#">接线端子选型手册</a>
------	--------------------------