




- 产品类型：插拔式端子,
- 接线方式：弹簧连接,
- 间距：7.50mm(7.62mm),
- 电压：300V,
- 电流：16A,
- 位数：2-12P

基本参数

间距(Pitch):	7.50mm(7.62mm)
电压(Rated voltage)-UL:	300V
电流(Rated current)-UL:	16A
电压(Rated voltage)-IEC:	630V
电流(Rated current)-IEC:	20A
线径(Wire range)-UL:	30-12AWG
线径(Wire range)-IEC:	0.2-2.5mm²sol/str 4mm²sol
位数(Pole number):	02~12P
绝缘材料(Insulation Material):	PA66 UL94 V-0
电流承载部件材料和镀层(Material & Plating of Current carrier):	Copper alloy, Tin plated
绝缘电阻(Insulation Resistance):	500MΩ or more at DC500V
耐电压(1分钟)(Withstanding Voltage/1Min):	3000V
额定冲击电压(Rated surge voltage):	6000V
接线螺丝(Wire clamp unit Screw), 最大扭矩(torque Max.):	M3, 0.5N·m
固定螺丝(Mounting Screw), 扭矩(torque):	M2.5, 0.2-0.25N·m
接线弹片材料(Material of Clamp spring):	-
剥线长度(Wire stripping length):	7.0mm
使用温度(Operating temperature):	-40℃ ~ +115℃
焊接方式(Soldering recommend):	-
认证(Approval):	

尺寸图



订购产品

产品名称	间距	位数	产品型号	3D下载	2D下载
插拔式端子	7.50mm	02~12P	SPA750-W00RL		
插拔式端子	7.62mm	02~12P	SPA762-W00RL		

资料下载

产品目录	接线端子选型手册
----------------------	--------------------------