




- 产品类型：多用途弹簧端子,
- 接线方式：弹片连接,
- 间距：5.00mm(.197" ),
- 电压：300V,
- 电流：15A,
- 位数：2-24P

基本参数

|                                                     |                                                                                                                                                                                                                                                             |
|-----------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 间距(Pitch):                                          | 5.00mm(.197" )                                                                                                                                                                                                                                              |
| 电压(Rated voltage)-UL:                               | 300V                                                                                                                                                                                                                                                        |
| 电流(Rated current)-UL:                               | 15A                                                                                                                                                                                                                                                         |
| 电压(Rated voltage)-IEC:                              | 320V                                                                                                                                                                                                                                                        |
| 电流(Rated current)-IEC:                              | 20A                                                                                                                                                                                                                                                         |
| 线径(Wire range)-UL:                                  | 22-14AWG                                                                                                                                                                                                                                                    |
| 线径(Wire range)-IEC:                                 | 2.5mm²                                                                                                                                                                                                                                                      |
| 位数(Pole number):                                    | 02~24P                                                                                                                                                                                                                                                      |
| 绝缘材料(Insulation Material):                          | PA66 UL94 V-0                                                                                                                                                                                                                                               |
| 电流承载部件材料和镀层(Material & Plating of Current carrier): | Copper alloy, Tin plated                                                                                                                                                                                                                                    |
| 绝缘电阻(Insulation Resistance):                        | 500MΩ or more at DC500V                                                                                                                                                                                                                                     |
| 耐电压(1分钟)(Withstanding Voltage/1Min):                | 2200V/1Min                                                                                                                                                                                                                                                  |
| 额定冲击电压(Rated surge voltage):                        | 4.0KV                                                                                                                                                                                                                                                       |
| 接线螺丝(Wire clamp unit Screw), 最大扭矩(torque Max.):     | -                                                                                                                                                                                                                                                           |
| 固定螺丝(Mounting Screw), 扭矩(torque):                   | -                                                                                                                                                                                                                                                           |
| 接线弹片材料(Material of Clamp spring):                   | -                                                                                                                                                                                                                                                           |
| 剥线长度(Wire stripping length):                        | -                                                                                                                                                                                                                                                           |
| 使用温度(Operating temperature):                        | -40℃ ~ +115℃                                                                                                                                                                                                                                                |
| 焊接方式(Soldering recommend):                          | Wave soldering, 260℃ 5S Max(Single Wave), 260℃ 10S Max(Double Wave)                                                                                                                                                                                         |
| 认证(Approval):                                       |    |

尺寸图



订购产品

| 产品名称    | 间距             | 位数     | 产品型号   | 3D下载 | 2D下载 |
|---------|----------------|--------|--------|------|------|
| 多用途弹簧端子 | 5.00mm(.197" ) | 02~24P | 45030X |      |      |

资料下载

|      |                          |
|------|--------------------------|
| 产品目录 | <a href="#">接线端子选型手册</a> |
|------|--------------------------|